



Natural Gas Generators
American Type Silent Type

FPC15K/ FPC20K/FPC25K

Feature:

- ★ Compact and unique design
- ★ four-cylinder, four-stroke, direct injection,
- ★ water cooled with emergency stop
- ★ low noise running

Model	SILENT SERIES		
	FPC15K	FPC20K	FPC25K
Rated Max.AC Power Output (kva)	13	18	20
Rated voltage(volts)	220, 230, 240, 220/380, 230/400, 240/415		
Rated frequency and speed(Hz/rpm)	50/3000	50/3000	50/3000
Power Fator	1(single phase) or 0.8(three phase)		
Connection type	1 phase,3 phase 4 wires		
Water tank capacity(L)	6.5		
Engine	liquid-cooled, 4-cylinder, In line, 4 stroke		
Type of Fuel	Natural Gas		
Operating Fuel Pressure	0.5 -1PSI		
Speed regulation	Electronic Governing		
Displacement(L)	1.1	1.3	2
Noise(dB/7m)	71		
Fuel Consumption@full load-m ³ /hr(Natural Gas)	5.3	7.65	9.26
Alternator model	SLG162F	SLG162G	SLG162G
Alternator type	Brushless self-excitation and constant voltage (AVR)		
Rotor/Stator insulation	H		
Dimensions(L×W×H)(mm)	1780*1020*1085	1880*1020*1085	1980*1020*1085
Weight(kg)	577	672	697

